

Page 1 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

UV-Additiv für CO2 50 ml TP-3826

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

Leak detector

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Dometic WAECO International GmbH, Hollefeldstr. 63, 48282 Emsdetten, Germany Phone:+49 (0) 2572 879 0, Fax:+49 (0) 2572 879 300 info@dometic-waeco.de, www.airconservice.de

Dometic UK Ltd Dometic House, The Brewery, DT11 9LS Blandford St Mary, Dorset, United Kingdom Phone:+44 (0) 0844 626 0133, Fax:+44 (0) 0844 626 0143 automotive@dometic.co.uk, www.airconstations.co.uk

Dometic UK Ltd Dometic House, The Brewery, DT11 9LS Blandford St Mary, Dorset, United Kingdom

Phone:+44 (0) 0844 626 0133, Fax:+44 (0) 0844 626 0143 automotive@dometic.co.uk, www.airconstations.co.uk

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(IRL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:

+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (CCWA)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Skin Sens. 1 H317-May cause an allergic skin reaction.

Aquatic Acute 1 H400-Very toxic to aquatic life.

Aquatic Chronic 2 H411-Toxic to aquatic life with long lasting effects.



Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H317-May cause an allergic skin reaction. H410-Very toxic to aquatic life with long lasting effects.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P333+P313-If skin irritation or rash occurs: Get medical advice / attention.

Polyether compounds

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**

0.=	
Polyether compounds	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	75-85
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

Soybean oil, Me ester	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	267-055-2
CAS	67784-80-9
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413

204-881-4
128-37-0
<1
_



Page 3 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

Decyloxirane	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	220-667-3
CAS	2855-19-8
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)

Dodecyloxirane	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	221-781-6
CAS	3234-28-4
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=10)

Tris(methylphenyl)phosphate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	215-548-8
CAS	1330-78-5
content %	<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Acute 1, H400 (M=1)
	Repr. 2, H361
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.



Page 4 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

reddening of the skin Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.



Page 5 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store at room temperature.

Store in a well-ventilated place.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

© Chemical Name	2,6-di-tert-butyl-p-cresol		Content %:<1
WEL-TWA: 10 mg/m3	WEL-STEL:		
Monitoring procedures:			
BMGV:		Other information:	
Chemical Name	2,6-di-tert-butyl-p-cresol		Content %:<1
OELV-8h: 10 mg/m3	OELV-15min:		
Monitoring procedures:			
BLV·		Other information:	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- © OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction.
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

8.2 Exposure controls

2,6-di-tert-butyl-p-cresol							
Area of application	Exposure route / Environmental	Effect on health	Descripto r	Value	Unit	Note	
	compartment						
	Environment - soil		PNEC	1,04	mg/kg wwt		
	Environment - sewage		PNEC	100	mg/l		
	treatment plant						
	Environment - sediment		PNEC	1,29	mg/kg wwt		
	Environment - marine		PNEC	0,4	μg/l		



Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

	Environment - periodic		PNEC	4	μg/l
	release				
	Environment - freshwater		PNEC	4	μg/l
	Environment - oral (animal feed)		PNEC	16,7	mg/kg
	Environment - soil		PNEC	1,23	mg/kg
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,74	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,8	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

>= 0,3

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If air supply is not sufficient, wear protective breathing apparatus.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



® ®L

Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Light brown Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Not determined Flash point: Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined

Density:

n.a. Bulk density: Not determined Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Viscosity: Not determined Explosive properties: Not determined Oxidising properties: Not determined

9.2 Other information

Not determined Miscibility: Not determined Fat solubility / solvent: Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

10.6 Hazardous decomposition products

No decomposition when used as directed.



BR.

Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

LIV Additive time CO2 50 mg	eaiiii eilecis,	See Section	Z. I (Classilica	uonj.		
UV-Additiv für CO2 50 ml						
TP-3826						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RĖ):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

2,6-di-tert-butyl-p-cresol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2930	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:					•	Slightly irritant
Serious eye				Rabbit	(Draize-Test)	Slightly irritant
damage/irritation:						
Respiratory or skin				Human being		Not sensitizising
sensitisation:						
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mammalian	in vitro	Negative
Reproductive toxicity:	NOAEL	100	mg/kg	Rat		
Specific target organ toxicity -	NOEL	25	mg/kg	Rat		(28 d)
repeated exposure (STOT-						
RE):						
Symptoms:						mucous
						membrane
						irritation

Decyloxirane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
1				Rabbit	Eye	Not imant



Page 9 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Respiratory or skin		Mouse	OECD 429 (Skin	No (skin
sensitisation:			Sensitisation - Local	contact)
			Lymph Node Assay)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation - Local	contact)
					Lymph Node Assay)	

Tris(methylphenyl)phosphate								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>3700	mg/kg	Rat		Analogous conclusion		
Acute toxicity, by dermal route:	LD0	10000	mg/kg	Rabbit		Analogous conclusion		
Acute toxicity, by inhalation:	LC50	11,1	mg/l/1h			Aerosol		
Skin corrosion/irritation:						Slightly irritant		
Serious eye damage/irritation:						Slightly irritant		
Respiratory or skin sensitisation:				Guinea pig		Negative		
Germ cell mutagenicity:					(Ames-Test)	Negative		
Carcinogenicity:						Negative		
Reproductive toxicity:						Positive		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	250	mg/kg	Rat				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

UV-Additiv für CO2 50 ml TP-3826								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	-						n.d.a.	
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to algae:							n.d.a.	
12.2. Persistence and							n.d.a.	
degradability:								
12.3. Bioaccumulative							n.d.a.	
potential:								
12.4. Mobility in soil:							n.d.a.	
12.5. Results of PBT							n.d.a.	
and vPvB assessment								
12.6. Other adverse							n.d.a.	
effects:								



Page 10 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001 Valid from: 06.06.2018

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Other information:		DOC-
		elimination
		degree(complex
		ing organic
		substance)>=
		80%/28d: n.a.

2,6-di-tert-butyl-p-cres Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>0,57	mg/l	J	QSAR	
12.1. Toxicity to fish:	NOEC/NOEL	42d	0,053	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	0,61	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,07	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,5	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	1	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4,5	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		330- 1800			, , , , , , , , , , , , , , , , , , ,	
12.3. Bioaccumulative potential:			230- 2500		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	56d
12.3. Bioaccumulative potential:	Log Pow		5,1				High
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge		·
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Decyloxirane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 11 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to daphnia:	EC50	48h	0,171	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,056	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,00416	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Dodecyloxirane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	EC50	72h	0,00236	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,00165	mg/l	Pseudokirchnerie	OECD 201	
				_	lla subcapitata	(Alga, Growth	
						Inhibition Test)	

Tris(methylphenyl)pho	Tris(methylphenyl)phosphate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	0,6	mg/l					
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,01	mg/l	Oncorhynchus mykiss				
12.1. Toxicity to daphnia:	EC50	48h	0,14	mg/l	Daphnia magna				
12.1. Toxicity to algae:	EC50	72h	0,4	mg/l	Desmodesmus subspicatus				
12.2. Persistence and degradability:			80	%					
12.3. Bioaccumulative potential:	BCF		144						
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance		
Toxicity to bacteria:	EC50		>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))			
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.		

SECTION 13: Disposal considerations



Page 12 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 99 wastes not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

3082

General statements

14.1. UN number:

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DECYLOXIRANE, DODE

CYLOXIRANE)

14.3. Transport hazard class(es):914.4. Packing group:IIIClassification code:M6LO:51

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DECYLOXIRANE, DODECYLOXIRANE

14.3. Transport hazard class(es):
14.4. Packing group:

EmS:
F-A, S-F
Marine Pollutant:

9
III
F-A, S-F

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (DECYLOXIRANE,DODECYLOXIRANE)

14.3. Transport hazard class(es):
9
14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code









Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be

considered according to storage, handling etc.):

to ite action and to extend by it action and extend to the control of the control										
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of							
		dangerous substances as	dangerous substances as							
		referred to in Article 3(10) for	referred to in Article 3(10) for							
		the application of - Lower-tier	the application of - Upper-tier							
		requirements	requirements							
E1		100	200							
E2		200	500							

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

0 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Acute 1, H400	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Skin Sens. — Skin sensitization



Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

Aquatic Acute — Hazardous to the aquatic environment - acute Aquatic Chronic — Hazardous to the aquatic environment - chronic

Skin Irrit. — Skin irritation Repr. — Reproductive toxicity

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential



Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSHNational Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative



® (RL)

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.06.2018 / 0001

Replacing version dated / version: 06.06.2018 / 0001

Valid from: 06.06.2018 PDF print date: 06.06.2018 UV-Additiv für CO2 50 ml

TP-3826

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.