

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
1/13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: 1,1,1,2-Tetrafluoroethane

Other Name: HFC-134a, R134a

Additional identification

Chemical name: Norflurane

Chemical formula: C₂H₂F₄

INDEX No. -

CAS-No. 811-97-2

EC No. 212-377-0

REACH Registration No. 01-2119459374-33

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Refrigerant. Transfilling gas or liquid, Using gas alone or in mixtures for the calibration of analysis equipment.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

BOC
Priestley Road, Worsley
M28 2UT Manchester

Telephone: 0800 111 333

E-mail: ReachSDS@boc.com

1.4 Emergency telephone number: 0800 111 333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure

Liquefied gas

H280: Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
2/13

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

EIGA-0783: Contains fluorinated greenhouse gases
EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards: Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Norflurane
INDEX No.:	-
CAS-No.:	811-97-2
EC No.:	212-377-0
REACH Registration No.:	01-2119459374-33
Purity:	100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

Trade name:	-
-------------	---

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
3/13

SECTION 4: First Aid Measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

SECTION 5: Firefighting Measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

SAFETY DATA SHEET
1,1,1,2-TetrafluoroethaneIssue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
4/13

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: carbon monoxide
; Carbonyl difluoride
; Hydrogen fluoride

5.3 Advice for firefighters**Special fire fighting procedures:**

In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for firefighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation.

6.4 Reference to other sections:

Refer to sections 8 and 13.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
5/13

SECTION 7: Handling and Storage:

7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities: Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Norflurane	TWA	1,000 ppm 4,240 mg/m3	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)

DNEL-Values

Critical component	type	Value	Remarks
Norflurane	Worker - inhalative, long-term - systemic	13936 mg/m3	-

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
6/13

PNEC-Values

Critical component	type	Value	Remarks
Norflurane	Aquatic (intermit. releases)	1 mg/l	-
	Sediment (freshwater)	0.75 mg/kg	-
	Sewage treatment plant	73 mg/l	-
	Aquatic (freshwater)	0.1 mg/l	-
	Aquatic (marine water)	0.01 mg/l	-

8.2 Exposure controls

Appropriate engineering controls: Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Eye/face protection: Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Wear working gloves while handling containers
Guideline: EN 388 Protective gloves against mechanical risks.

Body protection: No special precautions.

Other: Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls: For waste disposal, see section 13.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
7/13

SECTION 9: Physical And Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Colour:	Colorless
Odour:	faint ethereal
Odour Threshold:	Odour threshold is subjective and is inadequate to warn of over exposure.
pH:	not applicable.
Melting Point:	-108 °C Experimental result, Supporting study
Boiling Point:	-26 °C (101.3 kPa) Experimental result, Supporting study
Sublimation Point:	not applicable.
Critical Temp. (°C):	101 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability limit - upper (%):	not applicable.
Flammability limit - lower(%):	not applicable.
Vapour pressure:	5.74 bar (20 °C) Experimental result, Key study
Vapour density (air=1):	3.6
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	67 mg/l (25 °C)
Partition coefficient (n-octanol/water):	1.274
Autoignition Temperature:	> 743 °C Experimental result, Key study
Decomposition Temperature:	Dangerous; when heated to decomp they emit highly toxic fumes of hydrogen fluorides. Under certain conditions, fluorocarbon vapors may decomp on contact with flames or hot surfaces, creating potential hazard of inhalation of toxic decomp products.

Viscosity

Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidising Properties:	not applicable.

9.2 Other information:

Molecular weight: 102.03 g/mol (C₂H₂F₄)

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
8/13

SECTION 10: Stability and Reactivity

- 10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.
- 10.2 Chemical Stability:** Stable under normal conditions.
- 10.3 Possibility of Hazardous Reactions:** None.
- 10.4 Conditions to Avoid:** None.
- 10.5 Incompatible Materials:** No reaction with any common materials in dry or wet conditions.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

General information: None.

11.1 Information on toxicological effects

- Acute toxicity - Oral Product** Based on available data, the classification criteria are not met.
- Acute toxicity - Dermal Product** Based on available data, the classification criteria are not met.
- Acute toxicity - Inhalation Product** Based on available data, the classification criteria are not met.
- Repeated dose toxicity Norflurane** NOAEL (Rat(Male), Inhalation, 14 d): 100,000 ppm(m) Inhalation Experimental result, Supporting study
- Skin Corrosion/Irritation Product** Based on available data, the classification criteria are not met.
- Serious Eye Damage/Eye Irritation Product** Based on available data, the classification criteria are not met.
- Respiratory or Skin Sensitisation Product** Based on available data, the classification criteria are not met.
- Germ Cell Mutagenicity Product** Based on available data, the classification criteria are not met.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
9/13

Carcinogenicity
Product Based on available data, the classification criteria are not met.

Reproductive toxicity
Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure
Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure
Product Based on available data, the classification criteria are not met.

Aspiration Hazard
Product Not applicable to gases and gas mixtures..

Other Relevant Toxicity Information
Norflurane Cardiac sensitisation threshold limit
40000 ppm
Beagle (dog)NOAEC

Cardiac sensitisation threshold limit
80000 ppm
Beagle (dog)LOAEC

Light hydrocarbons like this one have been associated with cardiac sensitisation in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects. May produce irregular heart beat and nervous symptoms.

SECTION 12: Ecological Information

12.1 Toxicity

Acute toxicity
Product No ecological damage caused by this product.

Acute toxicity - Fish
Norflurane LC 50 (Oncorhynchus mykiss, 96 h): 450 mg/l (semi-static) Remarks: Experimental result, Key study

Acute toxicity - Aquatic Invertebrates
Norflurane EC 50 (Daphnia magna, 24 h): 960 mg/l (Static) Remarks: Experimental result, Key study

12.2 Persistence and Degradability
Product

Not applicable to gases and gas mixtures..

12.3 Bioaccumulative Potential
Product

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
10/13

12.4 Mobility in Soil
Product

Because of its high volatility, the product is unlikely to cause ground or water pollution.

Norflurane

Henry's Law Constant: 8,580 MPa (25 °C)

12.5 Results of PBT and vPvB
assessment
Product

Not classified as PBT or vPvB.

12.6 Other Adverse Effects:

Global Warming Potential

Global warming potential: 1,430
Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities, refer to container label.

Norflurane

EU Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 1430 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1: Hydrofluorocarbons (HFCs) and its mixtures

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

General information:

Avoid discharges to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Refer to manufacturer/supplier for information on recovery/recycling

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container:

14 06 01*: chlorofluorocarbons, HCFC, HFC

SECTION 14: Transport Information

ADR

14.1 UN Number:	UN 3159
14.2 UN Proper Shipping Name:	1,1,1,2-TETRAFLUOROETHANE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.2
Hazard No. (ADR):	20
Tunnel restriction code:	(C/E)

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
11/13

Emergency Action Code: **2TE**
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 3159
14.2 UN Proper Shipping Name: 1,1,1,2-TETRAFLUOROETHANE
14.3 Transport Hazard Class(es):
Class: 2
Label(s): 2.2
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 3159
14.2 UN Proper Shipping Name: 1,1,1,2-TETRAFLUOROETHANE
14.3 Transport Hazard Class(es):
Class: 2.2
Label(s): 2.2
EmS No.: F-C, S-V
14.3 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

IATA

14.1 UN Number: UN 3159
14.2 Proper Shipping Name: Refrigerant gas R 134a
14.3 Transport Hazard Class(es):
Class: 2.2
Label(s): 2.2
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -
Other information
Passenger and cargo aircraft: Allowed.
Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SAFETY DATA SHEET
1,1,1,2-TetrafluoroethaneIssue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
12/13**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:****National Regulations**

Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: CSA has been carried out.**SECTION 16: Other Information****Revision Information:** Not relevant.

Key literature references and sources for data: Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

- Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
- European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
- European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
- European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.
- International Programme on Chemical Safety (<http://www.inchem.org/>)
- ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
- Matheson Gas Data Book, 7th Edition.
- National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
- The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
- The European Chemical Industry Council (CEFIC) ERICards.
- United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
- Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
- Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication. EH40 (as amended) Workplace exposure limits.

SAFETY DATA SHEET
1,1,1,2-Tetrafluoroethane

Issue Date: 16.01.2013
Last revised date: 14.07.2017

Version: 1.2

SDS No.: 000010021750
13/13

Wording of the H-statements in sections 2 and 3

H280 Contains gas under pressure; may explode if heated.

Training information:

Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Last revised date:

14.07.2017

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.